

Datacentre 200kW Stackable Load Bank

Description

Model	Stackable Transportable
Country of Origin	United Kingdom
Max Capacity - Packaged Load Bank	200kW
Voltage Ranges - (Continuous Operation at Specified)	400V
Operating Frequency Range	50/60Hz
Test Supply Phases	3ph
Load Connections	Powersafe Connectors
Wires (Star Connection)	3
Load-Step Resolution @ Design Voltage	1kW
Voltage Tolerance (Short Term Operation)	+5%
Load Element Tolerance	+/-5%
Elements	80/20 nickel chrome resistance wire
Insulation Test	500V
Auxiliary Supply Voltage	220V - 240V
Auxiliary Supply Current	10A
Operating Frequency Range	50/60Hz
Phases	1ph
Electrical Protection	Thermal Emergency Cut Out Fan Overload Over Current Protection Emergency Stop
Control Voltage	Selectable - Test or Auxiliary
Cooling Method	Forced Air Cooling (Horizontal)
Air-Flow / Temperature Rise (Approx.)	6435 m ³ per hour / <100°C at outlet
Load Switching Category	AC-1 Resistive
Load Switching Contactor Type	3 Pole AC Contactors
Rated Maximum Ambient Temperature Operation	+50°C / +122°F
Rated Minimum Ambient Temperature Operation	-20°C / -4°F
Rated Maximum Relative Humidity	9500% RH
Altitude Rating	<500m [m.a.s.l.]
Noise level (Approx. @ 1m Free Field)	83dBA @ 50Hz

Enclosure

Material	Sheet Steel
Finish	RAL9002 Grey White
Control Chamber IP Rating	IP55
Lifting	Fork Lift Pockets
Protection Frame	Heavy Duty Rubber Bumper Pack

Enclosure Dimensions

Length (Approx.)	mm	1159
Width (Approx.)	mm	876
Height (Approx.)	mm	983
Total Weight (Approx.)	kg	275

Load Bank Control Systems

Control	VCS LC10
Optional Extras:	Extendable
- Control Extension Cable	10m
- Control Extension Cable	20m

200kW AC Stackable - June 24 (Changes to specification may vary without notice)

Crestchic VCS Control System for 200kW Loadbank



The Crestchic Versatile Control System, VCS, is an easy-to-use manual control system for small to medium resistive-only loadbanks. An advanced microprocessor-based system, VCS can be used to control single voltage loadbanks, or multiple units in parallel with the self-powered LC10 handheld controller. VCS offers the user the ability to set kW loads, whilst accurately displaying applied Power (kW) and Current (A) from the onboard instrumentation module. Loads can be applied in three different ways:

Follow

This application setting is perfect for data centre heat-load testing, as the entire load is evenly distributed across all loadbanks generating an equal heat-load for commissioning purposes.

Proportional

Any given load is precisely applied across multiple loadbanks even when the total kW amount is not evenly divisible across the number of loadbanks in use. Ideal for high precision total load, or where the loadbanks in use are of unequal size.

Overflow


A traditional control set-up for load testing generators, whereby the load is applied to the first loadbank until its capacity is reached, before applying the remaining load to the next loadbank(s) in-line, until maximum selected load is reached.

Key Features:


- AC loadbank control system for resistive-only operation (kW)
- Single or multiple loadbank operation from an individual controller (up to 20 loadbanks or 4.0MW)
- Automatic IP assignment of each loadbank to the controller
- Multiple load sharing programme: Follow, Proportional and Overflow
- Typical load resolution of 1kW across the loadbank range
- 0 to 100% load application or load rejection
- Load application in kW or Amps
- Display of Ph-N voltage with kW and Current, both per phase and total
- Ethernet 10/100 BASE-T communication to loadbanks



Front View



Side View



Quality without compromise

Our load banks are characterised by one thing above all: quality. At every stage of our supply chain, from raw material to finished item, we work with established, worldclass suppliers and implement our own uncompromising quality control processes to ensure that our products perform better and last longer.



For further information contact:
 Crestchic (UK) Limited
 Second Avenue, Centrum 100
 Burton-on-Trent, DE14 2WF
 United Kingdom

Tel +44 (0) 1283 531645
 sales.uk@crestchic.com
 hires.uk@crestchic.com

www.crestchicloadbanks.com

The information given in this literature is, to the best of our knowledge, correct at the time of going to print. However, Crestchic is constantly looking at ways of improving their products and services and therefore reserve the right to change, without prior notice, any of the data contained in this publication. Any orders placed will be subject to our Standard Conditions of Sale or Rental, available on request.